

COMBO FL-5545T-C



Technical features

- ✘ High temperature and sticky free L bar sealing knife, sealing action without smoking and burned. Sealed part is tidy and clean.
- ✘ Conveyor belt is adjustable on the high by a hand roller.
- ✘ There is a manual/auto switch. When choose auto function, Whole sealing action controlled by cylinder automatically, with fast packing speed.
- ✘ Safety protection device is set on the sealer, in case of the sealing knife cut hands.
- ✘ Main parts are import from famous brand, which guarantee a long using life.

Scope of Application

Suitable of electrical products, hardwares, softwares, food, printing products, medications, floor boards, ceramics etc's packing.

Suitable for PVC, POF, PP film's using.

- ✘ Technical features of shrink tunnel
- ✘ Save the high temperature on the heating wire, then the motor fan blow the air in the tunnel make it circulate inside tunnel. By this way, temperature of inside tunnel goes up fast and small lost.
- ✘ Output can reach to 20000-30000per day.
- ✘ Conveyor rollers are covered by silica tubes, which guarantee a long using life.
- ✘ Motor is from famous manufacture, which guarantee a long work tim per day.
- ✘ Triple hot insolate layers make sure the average power is only 4-5kw.
- ✘ Conveyor speed is controllable in 1-10m per minute.
- ✘ Foot-wheels make machine movable easily .

Suitable for PVC, PP, POF film use.

Model	COMBO FL-5545T-C
Machine dimension L×W×H□mm□	2569×764×1612
Max packing size L×W×H□mm□	400×300×200
Max sealing size L×W×H□mm□	550×450
Packing speed(pcs/h)	800-1200
Net weight □kg□	285
Power □kw□ / Air pressure(kg/cm)	5.5
Power supply	1φ110V/220V 50/60Hz